



MATERIAL SAFETY DATA SHEET

Hazard Rating	NEPA	
4-Extreme	Toxicity	1
3-High	Fire	2
2-Moderate	Reactivity	0
1-Slight	Special	
0-Insignificant		

PRODUCT NAME: **BETTER WAX** **CAA126**

SECTION 1

Manufacturer Information: L & C Enterprises, L. M. A.
2357 Hwy. 53
Poplarville, MS 39470
Phone No.: 601-795-4147 Emergency Phone No. INFOTRAC: 800-535-5053
Fax No.: 601-795-2111

SECTION II - Hazardous Ingredients/Identity/Information

Hazardous Components
Specific Chemical Identity: Common Name(s) OSHA PEL ACGIH TLV Other %
Odorless Mineral Spirits CAS# 64742-48-9 100 ppm TWA
200 ppm TWA

SECTION III - Physical/Chemical Characteristics

Boiling Point: 220 Degrees F
Specific Gravity (Water = 1): 0.9916
Vapor Pressure (mm Hg): N/A
Melting Point: N/A
Vapor Density (Air = 1): > 1
Evaporation Rate (butyl Acetate = 1): 1
Appearance and Odor: Pale Yellow Creamy Liquid (Banana Scent)
Solubility in Water: 100%

SECTION IV - Fire and Explosion Hazard Data

Flash Point (Method Used): 121 TCC Flammable Limits LEL UEL
Extinguishing Media, carbon dioxide, water foam ND ND
Special Fire Fighting Method: SCBA should be used in fighting fires involving chemicals.
Unusual Fire and Explosion Hazards: None Known

SECTION V - Reactivity Data

Stability: Stable Conditions to Avoid: Excessive heat
Incompatibility (Materials to Avoid): Strong acids or bases, oxidizing agents.
Hazardous Decomposition's or Byproducts: Combustion may yield carbon monoxide and/or carbon dioxide. Hazardous Polymerization: Will Not Occur

SECTION VI - Health Hazard Data

Route(s) of Entry: Inhalation? Yes Skin? Yes Ingestion? Yes
Health Hazards (Acute and Chronic): Can cause eye irritation. Excessive inhalation may cause respiratory irritation. Prolonged skin contact may cause slight irritation. Ingestion can cause gastrointestinal irritation.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	Not Listed	Not Listed	Not Listed

Signs and Symptoms of Exposure: Irritation, redness.

Medical Conditions Generally Aggravated by Exposure: Pre-Existing skin conditions may be aggravated. Emergency and First Aid Procedures: Eye - Flush with water for 15 minutes, see physician if irritation persists. Skin - Wash with soap and water, see physician if irritation persists. Inhalation - Remove to fresh air. Ingestion - Do not induce vomiting, call physician.

SECTION VII - Precautions for Safe Handling and Use

Steps to be taken in case material is released or spilled:

Use absorbent material to collect and contain for disposal. Wash spill area with soap and water. Waste disposal method in accordance with Federal, State and local regulations.

Precautions to be taken in handling and storing: Avoid strong oxidizing materials store in well ventilated area. Keep containers closed when not in use. Do not store near heat or open flame.

Other precautions: Keep out of the reach of children. Do not get in eyes or on skin.

SECTION VIII - Control Measures

Respiratory Protection (Specify Type): Dust mask, use SCBA when exposure levels are exceeded.

Ventilation: Local Exhaust: Special:

Mechanical: Recommended Other:

Protective Gloves: Rubber or Neoprene Eye Protection: Approved Safety Glasses

Other Protective Clothing: None required in normal use.

Work Hygienic Practices: Observe good housekeeping practices.

KEEP OUT OF REACH OF CHILDREN