



MATERIAL SAFETY DATA SHEET

Hazard Ratings		Health	1
4-Extreme	1-Slight	Fire	2
3-High	0-Insignificant	Reactivity	0
2-Moderate	X-See Text	Specific	X

Manufacturer Information: L & C Enterprises, L. M. A.
2357 Hwy. 53
Poplarville, MS 39470
Emergency Phone No. INFOTRAC: 800-535-5053

Phone No.: 601-795-4147
Fax No.: 601-795-2111

SECTION 1: IDENTIFICATION

PRODUCT NAME: BLUE MAGIC CAC125

SECTION 2: HAZARDOUS INGREDIENTS

NAMES OF HAZARDOUS INGREDIENTS: See CFR29 1910.1200 (i)-(13)

CHEMICAL/COMMON NAME	CAS#	PERCENTAGE	PEL-OSHA	TLV-ACGIH
Mineral Spirits	8052-41-3	>1	100PPM	100PPM

THIS PRODUCT HAS NO CARCINOGENS (NTP, IARC, OSHA):

SECTION 3: HEALTH HAZARD DATA

HEALTH EFFECTS (Acute and Chronic):

ACUTE a) Eyes---Can cause severe irritation, redness, tearing, blurred vision
b) Skin---Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.
c) Inhalation---Mild irritation.
d) Ingestion---Can cause gastro-intestinal irritation, nausea, vomiting and diarrhea.

CHRONIC a) Inhalation may increase susceptibility to respiratory illness.

PRIMARY ROUTES OF ENTRY:
a) Skin b) Inhalation

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:
Pre-existing skin, eye and respiratory disorders may be aggravated by exposure to product.

EMERGENCY FIRST AID PROCEDURES:
a) Skin--Immediately flush skin with lots of running water for at least 30 minutes. Remove contaminated clothing and shoes. Wash before reuse.
b) Eyes--Flush immediately with large quantities of running water for at least 15 minutes. Consult physician. c) Inhalation--If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet and get medical attention. d) Ingestion--Do not induce vomiting. Call physician immediately. If conscious give lots of water or milk. Do not give anything by mouth to an unconscious or convulsing person.

SECTION 4: CHEMICAL DATA

BOILING POINT (F).....:	> 240	SPECIFIC GRAVITY (WATER-1).....:	0.795
VAPOR PRESSURE (mmHg):	2	PERCENT VOLATILE BY VOLUME (%):	85.00
VAPOR DENSITY (AIR=1):	4.9	EVAPORATION RATE (WATER=1).....:	24
SOLUBILITY IN WATER:	Insoluble.		
APPEARANCE AND ODOR INFORMATION:		Thin blue liquid with a melon odor.	

SECTION 5: PHYSICAL HAZARD DATA

FLASH POINT (Method Used): 108 degrees FTCC FLAMMABLE LIMITS: LEL=0.9% UEL = 6% EXTINGUISHING MEDIA: Regular foam, water fog, carbon dioxide or dry chemicals.

SPECIAL FIRE FIGHTING PROCEDURES: a) Clear fire area of unprotected personnel. Do not enter confined fire area without full bunker gear, including a positive pressure mode breathing apparatus. Cool fire exposed containers with water fog.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and may travel along the ground or by ventilation and ignite by heat, pilot lights and other flames in locations distant from the material handling point. See additional comments.

INCOMPATIBILITY (Material to avoid): Avoid contact with strong oxidizing agents such as permanganate, chlorine, etc.

HAZARDOUS DECOMPOSITION PRODUCTS: Burning may produce oxides of carbon and traces of hydrocarbons.

HAZARDOUS POLYMERIZATION WILL NOT OCCUR. THIS PRODUCT IS STABLE

SECTION 6: SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate all ignition sources. Absorb on suitable absorbent and shovel into containers. WASTE DISPOSAL METHODS: Contaminated absorbent may be disposed of according to local, state and federal regulations for products containing petroleum distillates.

SECTION 7: EXPOSURE CONTROL INFORMATION

VENTILATION:

LOCAL EXHAUST: Below TLV(s) MECHANICAL (General): Explosion Proof
SPECIAL.....: N/A OTHER.....: N/A

RESPIRATORY PROTECTION: An appropriate NIOSH approved hydrocarbon canister or respirator for organic is advised of proper en environmental control.

OTHER PROTECTIVE EQUIPMENT:

- a) To prevent repeated and prolonged skin contact, wear impervious clothing and boots.
- b) Eye wash and quick drench facilities..

OTHER ENGINEERING CONTROLS: None Known. WORK PRACTICES: Eye wash fountain and safety shower should be easily accessible. Discard properly such items as rags and trash soaked with the product. Provide adequate ventilation.

HYGIENIC PRACTICES: Avoid contact with eyes, skin and clothing. Avoid inhalation of product vapors. Wash thoroughly after handling and before eating, drinking or smoking. Remove contaminated clothing promptly and wash before reuse

SECTION 8: SPECIAL PRECAUTION

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

- a) Keep away from heat, sparks and open flames.
- b) Do not store under freezing conditions or above 120 degrees F.
- c) Protect from physical damage and keep tightly closed.
- d) Do not store near acids or acidic materials and oxidizers.
- e) Containers mark NA 1993

MAINTENANCE PRECAUTIONS: When working with FLAMMABLE material electrically ground all equipment and use only non-sparking tools.

OTHER PRECAUTIONS: a) Containers, even those that have been emptied will retain product residue and vapors. Always obey hazard warnings. b) Always ground metal containers while pouring.

OTHER ADDITIONAL COMMENTS: a) Never use welding or a cutting torch on or near container (even empty) because product (even just residue) can ignite explosively. b) All 5 gallon pails and larger metal containers should be grounded when material is transferred.

SHIPPING INFO, UN/NA #'s, Secondary container label INFO NECESSARY OR SUGGESTED: COMBUSTIBLE LIQUID N. O. S. UN 1993, PG III, NO LABELS REQUIRED.

KEEP OUT OF THE REACH OF CHILDREN

