



MATERIAL SAFETY DATA SHEET

Manufacturer Information:

L & C Enterprises, L. M. A.

2357 Hwy. 53

Poplarville, MS 39470

Emergency Phone No. INFOTRAC: 800-535-5053

Phone No.: 601-795-4147

Fax No.: 601-795-2111

SECTION 1 PRODUCT IDENTIFICATION

PRODUCT NAME: **BUMPER COTE**

CAC133

SECTION 2 HAZARDOUS INGREDIENTS

Hazardous Chemical Name:	Percent in Product	PEL/OSHA	TLV-ACGIH	CASE #	Carcinogen
Not Regulated		NA	NA	NA	NA

SECTION 3 PHYSICAL DATA

Boiling Point: >300 F
Specific Gravity: 0.975
Vapor Pressure: <1.lb.
Volatile: NE
Vapor Density: 1.3
Solubility: Insoluble
Evaporation Rate: NE
App/Odor: See Section 1

SECTION 4 FIRE AND EXPLOSION DATA

NFPA CODES: Health: 0 Flammability: 1 Reactivity: 0 Flash Point: > 275 F
Extinguishing Media: Regular foam, water fog, carbon dioxide, or dry chemicals
Hazardous Decomposition: Oxides of carbon or traces of hydrocarbons may be formed in small amounts. Special Fire Fighting Procedures: Clear the area of personnel. Do not enter confined area without full bunker gear and positive pressure breathing apparatus.
Unusual fire/explosion hazards: None

SECTION 5 HEALTH HAZARD DATA

Permissible Exposure Level: See Section 2 under PEL/OSHA

Effects of Overexposure (Acute/Chronic): Eyes: Can cause moderate irritation, redness, tearing, and blurred vision. Skin: Prolonged or repeated exposure can cause moderate irritation, defatting of the skin or dermatitis. Inhalation: Fine mist may cause irritation of the nose and throat.

Ingestion: Gastrointestinal irritation, nausea, vomiting, and signs of nervous system depression.

FIRST AID PROCEDURES:

Eyes: Wash eyes immediately with large amounts of water. Get medical attention immediately **DO NOT USE** contact lenses while using this product.

Skin: Wash contacted areas with mild soap and water.

Inhalation: Move person to fresh air at once. If breathing has stopped, get medical attention immediately.

Ingestion: Do not induce vomiting. If person is conscious, give water. Get medical attention.

Primary route of entry: Inhalation, Eyes.

SECTION 6 REACTIVITY

Incompatibility: Strong oxidizing agents or acid.

Hazardous Polymerization: Will Not Occur.

Stability: Stable

SECTION 7 SPILL OR LEAK PROCEDURES

Remove all sources of ignition. Ventilate area. Absorb with an inert absorbent material.

All used and unused product should be disposed of in conformance with local, state and federal regulations.

SECTION 8 PROTECTIVE EQUIPMENT TO BE USED

If PEL or TLV limits, listed in Section 2, are exceeded a NIOSH/OSHA approved respirator is advised. These respirators should not be used for an extended period of time. A dust mask should be used when using a buffing machine. High speeds of buffing machines throw chemical dust into the air. Sufficient mechanical ventilation should be used to maintain exposure levels below PEL and TV limits in Section 2. Chemical resistant gloves are always recommended as some chemicals may not only do damage to the skin but may also be a threat through absorption. Chemical resistant splash goggles are recommended when using liquid chemicals, or using a high speed buffing machine.

SECTION 9 SPECIAL PRECAUTIONS

Store materials in a cool dry place away from heat and open flame. Clothing being used around chemicals should be cleaned daily. Never weld on or near containers either empty or full. Secure all chemicals out of the reach of children. Use proper safety equipment at all times.

Disclaimer of Liability: The information contained herein is based on data considered to be accurate. However, the information is provided without any warranty, expressed or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of this product.

KEEP OUT OF REACH OF CHILDREN